

WPC -132-I-M

Part No:MPEth-TCP/IP-WPC-132-I-M



SPEC

- CPU : 32-bits ARM-7 Winbonds CPU , 80 MHz
- RAM : 8 M Bytes SDRAM
- ROM : 4 M Bytes Flash ROM (2M for User Programming)
- OS : uC-Linux OS , Provide API,CGI for Customer Programming
- Ethernet
 1. Port Type : RJ-45 Connector
 2. Speed : 10 /100 M bps (Auto Detecting)
 3. Protocol : ARP , IP , ICMP , UDP , TCP , HTTP , DHCP
 4. Protocol : PPPoE , DDNS , NTP , FTP , Telnet
 5. Mode : TCP Server / TCP Client / UDP
 6. Setup : HTTP Browser Setup (IE & Netscape) , Console
 7. Security : Setup Password
 8. Protection : Built-in 1.5KV Magnetic Isolation
- Serial Port
 1. Port : RS-232 / 422 / 485 * 1 Port (3000 V DC
 2. Photo couple isolation Protect)
 3. Speed : 300 bps ~ 230.4 K bps
 4. Parity : None , Odd , Even , Mark , Space
 5. Data Bit : 5 , 6 , 7 , 8
 6. Stop Bit : 1 , 2
 7. RS-232 Pins : Rx , Tx , GND , RTS , CTS , DTR ,
 8. DSR , DCD

9. RS-422 : Rx+ , Rx- , Tx+ , Tx- (Surge Protect)
10. (Over current protect)
11. RS-485 : Data+ , Data- (Surge Protect)
(Over current protect)
12. 15KV ESD for all signals
13. Digital Input / Output : TTL * 9 Pins
14. Programmable Digital Input / Output * 9 Pins
15. USB (Host * 1 port) : for Memory Storage
16. Watch Dog Function
17. Power : DC 9~30 V , 1000 mA 500mA@12V
18. Led Lamp : SYS (PWR) , LAN , LED 1 , LED 2
(User Define)
19. Environment :
Operating Temperature: 0°C ~70°C
Storage Temperature : -10°C ~80°C
20. Dimensions : 110 * 60 * 20 mm (W * D * H)
21. Weight : 80 gm
22. RoHS : Compliant with RoHS
23. Regulatory Approvals : EMC : FCC Class A, CE Class A
24. WARRANTY : 1 year



標高電子股份有限公司

Microport Computer Electronics Inc.

Tel/06-2753783 Fax/06-2375031

<http://www.microporttaiwan.com>